

External antenna for Novatel connect card

824 ÷ 960 / 1710 ÷ 2170MHz, 2dBi

T01111970



Electrical Specifications

Frequency Band	MHz	824 ÷ 960 1710 ÷ 2170
Impedance	Ω	50
Polarization		vertical
Gain	dBi	2
VSWR		1 : 3
Continuous max power	W	10
Operating temperature range	°C	-40 ÷ +70

Mechanical Specifications

Connector		RF mini
Cable lenght	mm	50
Dimensions	mm	174 x 26.2 x 11
Colour		black
Weight	g	160
Mounting		adhesive strip
Packaging		G3 cardboard + bag

EXTERNAL ANTENNA FOR 3G CONNECT CARD

Instruction of use

In order to properly use the antenna and obtain the best efficiency we suggest to install it vertically on the chosen support.

Recommendations

Please be careful not to damage the connector of the antenna by forcing it in the card.
Do not leave the antenna exposed to heat for a long period of time or on the dashboard of a car or in a humid and dusty place.

The product is not waterproof, therefore do not leave it in places where it risks getting wet.



Important information regarding RF exposure:
To assure compliance with Radio and Telecommunications Terminal Equipment Directive 1999/5/EC all units when connected to Mobile Connect card must be used in operation, requires a minimum of 2.5cm separation from the head and any part of the body.